



PRODUCT DATA

**SELENIUM SAE 10W30
API SN/GF-5**

**MINERAL BLEND LUBRICANT
PETROL**

DESCRIPTION

FleetOil Selenium 10W-30 SN/GF-5 Mineral based is the superior grade petrol engine oil. This oil is formulated with mineral base utilizing latest additive technology to provide optimum performance in today's modern high output petrol engine. The oil is enhanced by the selection of thermally stable base oils, oxidation inhibitors, viscosity improvers and detergents. The level of dispersant and detergent additives in the oil contributes to the maintenance of the cleanliness of the engine under all service conditions. The special additives inhibit the formation of sludge especially under the constant cold temperature operation of urban driving.

APPLICATION

FleetOil Selenium 10W-30 SN/GF-5 is a premium mineral passenger car motor oil formulated using highly refined based oils and an optimized additive systems to give a year around performance in today's most petrol powered engines, van and light trucks.

BENEFITS

- Protection against corrosion.
- A very good shear stability.
- A very high oxidation stability.
- An excellent viscosity temperature behaviour.
- Convincing detergent and dispersant attributes

Radifleet

PRODUCT PERFORMANCE CLAIM

FleetOil Selenium 10W-30 SN/GF-5 surpasses a wide range of specifications and is suitable where the following requirements are called for:

- API Petrol: SN, (SM,SL,SJ, SH and all superseded classifications) / API Diesel: CF, CD
- ILSAC GF-4

TYPICAL CHARACTERISTICS

NAME	METHOD	UNIT	SELENIUM 10W30 SN/GF-5 (SAE J 300)
Density @ 15°C	ASTM D1298	Kg/ltr	0.872
Viscosity @ 100°C	ASTM D445	cSt	11.2
Viscosity @ 40°C	ASTM D445	cSt	77.8
Viscosity Index	ASTM D2270	None	132
Flash Point, minimum	ASTM D92	°C	228

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Radifleet or its distributors and agent for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.



Radifleet Sdn Bhd | Lot 137/138 Jalan 28/10A Taman Perindustrian IKS (MIEL) 68100 Kuala Lumpur | Tel: +60361871276 | www.radifleet.com.my