



PRODUCT DATA

**SELENIUM SAE 15W40
API SM/CF**

**MINERAL BLEND LUBRICANT
PETROL**

DESCRIPTION

FleetOil Selenium 15W-40 SM/CF is a premium quality engine oil made using the latest premium technology base oils. Its high temperature performance is enhanced by the use of thermally stable base Oils, oxidation inhibitors, viscosity improvers and detergents. The level of dispersants and detergents in the oil maintains the engine in a much cleaner condition under all service conditions. These special additives inhibit the formation of sludge, especially under the constant cold temperature operation of urban driving.

APPLICATION

FleetOil Selenium 15W-40 SM/CF is a highly superior mineral petrol engine oil specially designed for severe petrol and moderate duty diesel engines for mixed fleets. It is developed using an advanced premium mineral passenger car motor oil formulated using highly refined base oils for maximum lubrication and protection..

BENEFITS

- Excellent wear protection
- Excellent deposit control and engine cleanliness
- Excellent thermal and oxidation stability

PRODUCT PERFORMANCE CLAIM

FleetOil Selenium 15W-40 SM/CF F surpasses a wide range of specifications and is suitable where the following requirements are called for:

- API Petrol: SM, (SL,SJ, SH and all superseded classifications)
- API Diesel: CF, CD

TYPICAL CHARACTERISTICS

NAME	METHOD	UNIT	SELENIUM 15W40 SM/CF (SAE J 300)
Density @ 15°C	ASTM D1298	Kg/lit	0.877
Viscosity @ 100°C	ASTM D445	cSt	14.5
Viscosity @ 40°C	ASTM D445	cSt	113.1
Viscosity Index	ASTM D2270	None	131
Flash Point, minimum	ASTM D92	°C	230

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Radifleet or its distributors and agent for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.



Radifleet Sdn Bhd | Lot 137/138 Jalan 28/10A Taman Perindustrian IKS (MIEL) 68100 Kuala Lumpur | Tel: +60361871276 |

www.radifleet.com.my