



PRODUCT DATA

SELENIUM SAE 20W50
API SL/CF

MINERAL BLEND LUBRICANT
PETROL

DESCRIPTION

FleetOil Selenium 20W-50 SL/CF is a high performance mineral passenger car engine oil specially formulated using high quality base oils and an advanced additive system to provide optimum protection, wear control and stable stay-in-grade viscosity.

APPLICATION

FleetOil Selenium 20W-50 SL/CF exceeds SL/CF rated performance, and is strongly recommended for all multi-valve and modern engines where a low temperature viscosity is required by the engine manufacturer for cold crank starts, but still providing protection in the tropical heat. Although it was specifically designed for post-1997 model motors, including multi-valve and turbo-charged motors, it is also suitable for light duty passenger car style diesel motors.

BENEFITS

- Good deposit and wear protection
- Good oxidation, thermal stability sludge control
- Good stay-in-grade viscosity shear stability.

PRODUCT PERFORMANCE CLAIM

FleetOil Selenium 20W-50 SL/CF surpasses a wide range of specifications and is suitable where the following requirements are called for:

- API Petrol: SL, (SJ, SH and all superseded classifications)
- API Diesel: CF, CD

TYPICAL CHARACTERISTICS

| NAME | METHOD | UNIT | SELENIUM 20W50 SL/CF (SAE J 300) |
|----------------------|------------|------|----------------------------------|
| Density @ 15°C | ASTM D1298 | Kg/l | 0.878 |
| Viscosity @ 100°C | ASTM D445 | cSt | 19.1 |
| Viscosity @ 40°C | ASTM D445 | cSt | 176.3 |
| Viscosity Index | ASTM D2270 | None | 123 |
| Flash Point, minimum | ASTM D92 | °C | 236 |

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Radifleet or its distributors and agent for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.



Radifleet Sdn Bhd | Lot 137/138 Jalan 28/10A Taman Perindustrian IKS (MIEL) 68100 Kuala Lumpur | Tel: +60361871276 | www.radifleet.com.my