



PRODUCT DATA

**THALLIUM SX 10W40
API SM**

**SEMI SYNTHETIC 4T
MOTORCYCLE LUBRICANT**

DESCRIPTION

FleetOil THALLIUM SX - Semi Synthetic 10W-40 is a blend of high quality base stocks and an exclusive high performance additive package that ensures minimum drag, extended engine life, longer oil life and easy cold weather starting

APPLICATION

FleetOil THALLIUM SX - Semi Synthetic 10W-40 is suitable for motorcycles built in Europe and in Japan for which the JASO MA specifications are recommended. The product is recommended for all motorcycles where API SL or JASO MA fluids are specified.

BENEFITS

- Lower oil temperatures for longer oil life and less metal fatigue
- High lubricity for faster acceleration and more RPM's
- Protects against oil cavitation (foaming), a must for high revving engines
- Slows oil burning and raises oil pressure in worn engines.

PRODUCT PERFORMANCE CLAIM

FleetOil THALLIUM SX - Semi Synthetic 10W-40 surpasses a wide range of specifications and is suitable where the following requirements are called for:

- API SM
- JASO MA

TYPICAL CHARACTERISTICS

NAME	METHOD	UNIT	THALLIUM SX 10W40 SM (SAE J 300)
Density @ 15°C	ASTM D1298	Kg/ltr	0.8645
Viscosity @ 100°C	ASTM D445	cSt	14.11
Viscosity @ 40°C	ASTM D445	cSt	90.0
Viscosity Index	ASTM D2270	None	160
Flash Point, minimum	ASTM D92	°C	210

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Radifleet or its distributors and agent for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.



Radifleet Sdn Bhd | Lot 137/138 Jalan 28/10A Taman Perindustrian IKS (MIEL) 68100 Kuala Lumpur | Tel: +60361871276 |
www.radifleet.com.my