



## PRODUCT DATA

**ZYLIUM SAE 5W30  
API SN : ACEA A5/B5**

**FULLY-SYNTHETIC LUBRICANT**

### DESCRIPTION

**FleetOil Zylum 5W-30 SN, ACEA A5/B5** is a fully synthetic engine oil scientifically developed using advanced base stocks and a proven performance additive technology to impart superior lubrication for maximum protection, fuel efficiency and controlled emission with its full SAPs compliance. The oil meets the 2010 edition of the ACEA specifications in that it has improved sludge handling performance to further increase it's the long drain capabilities

### APPLICATION

**FleetOil Zylum 5W-30 SN, ACEA A5/B5** is intended for use at extended drain intervals in petrol engines and car and light van diesel engines. These engines will be designed to be capable of using this low friction low viscosity oil with a High Temperature / High Shear Rate

### BENEFITS

- Outstanding thermal and oxidation stability permitting extended drain interval protection
- Excellent stay-in-grade viscosity providing maximum performance
- Optimized frictional properties to provide excellent fuel economy

### PRODUCT PERFORMANCE CLAIM

**FleetOil Zylum 5W-30 SN, ACEA A5/B5** meets or exceeds:

- ACEA: A5/B5 and below
- API Diesel: CJ-4, CI-4, CH4, CF
- API Petrol: SN, (SM, SL, SJ, SH and all superseded classifications)
- RN O700

### TYPICAL CHARACTERISTICS

NAME	METHOD	UNIT	ZYLIUM 5W30 SN : ACEA A5/B5 (SAE J 300)
Density @ 15°C	ASTM D1298	Kg/ltr	0.851
Viscosity @ 100°C	ASTM D445	cSt	10.7
Viscosity @ 40°C	ASTM D445	cSt	60.1
Viscosity Index	ASTM D2270	None	170
Flash Point, minimum	ASTM D92	°C	220

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Radifleet or its distributors and agent for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.



Radifleet Sdn Bhd | Lot 137/138 Jalan 28/10A Taman Perindustrian IKS (MIEL) 68100 Kuala Lumpur | Tel: +60361871276 | [www.radifleet.com.my](http://www.radifleet.com.my)